GRAIN CART

Farm King

Models 1060 and 1360









PRODUCT OVERVIEW

- Increase harvest efficiency with a Farm King Grain Cart
- Model 1360 1360 bu Model 1060 - 1060 bu

FEATURES

- **Direct Drive Augers**
- Rotating Unload Spout
- Halogen work light
- 22" Unloading Auger

OPTIONS

- AgCam rear-facing mount kit
- Digistar GT400 and GT460 scale kits

AVAILABLE COLORS*













GRAIN CART Models 1060, 1360



Direct Drive Augers

Farm King grain carts do not require hydraulic flow to operate the unload auger or the floor drag auger. The floor drag auger is belt driven off of the PTO. The unloading auger is driven directly through a gearbox. Direct drive augers eliminate the use of chains and sprockets required for auger drives, helping increase productivity and reduce downtime.

Floor Drag Auger

A floor drag auger is standard equipment on the 1060 and 1360. Farm King grain carts are able to unload smoothly and

quietly by consistently feeding grain into the unload auger. Operator engaged hydraulic gates regulate the flow of grain to the drag auger.

Gravity Flow Discharge

The Farm King 1060 and 1360 feature a gravity flow discharge door located at the bottom of the unload auger. A manual engagement allows operators to fill pits and auger hoppers with ease.

Corner Mounted Auger

A corner-mounted auger improves operator visibility and provides easier cleanout. By

mounting the auger on the front of the cart spillage and operator fatigue are reduced.

Large Bin Design

Both the 1060 and 1360 have a large bin and low center of gravity. The low center of gravity provides stability for the cart while maintaining a bin wall height of less than 13'.

Access

The gravity flow discharge makes for simple accessible cleanout of the lift auger. A bin ladder provides easy operator access to the top of the bin and cart.



The Farm King grain cart builds on decades of high quality grain handling manufacturing experience. Using a Farm King grain cart helps maximize the productivity of your harvest operation. The 1060 and 1360 bushel grain carts from Farm King feature a high capacity 22" unloading auger, standard roll tarp and a rotating unload spout. A gravity flow discharge allows the cart to unload directly into pits and auger hoppers. Both the 1060 and 1360 are available with walking tandem axle duals.

[1] Corner auger with rotating auger spout [2] Gravity flow discharge [3] Hydraulic flow gates

[4] AgCam rear-facing mount camera option [5] Farm King grain carts are available from factory with two scale system options. Built by Digi-Star the GT400 is a simple easy to use scale system. The GT460 scale allows the operator to log data and export it to a USB. (GT460 shown)









Warranty

Farm King grain carts come with a comprehensive two-year parts and service warranty.

Auger Flighting and Tubes

All Farm King grain carts are built to last using high quality designs and components. The Unload auger uses 5/16" flighting and

the floor drag auger uses 1/4" flighting. A heavy, seven gauge tube is used for the unload auger and another seven gauge reinforcing sleeve is used on the first 52" of the unloading auger tube.

SPECIFICATIONS

TIRE OPTIONS

Model 1060

- Single Axle w/ high flotation
- Walking tandem axle w/ dual row crop tires

Model 1360

Walking tandem axle w/ dual row crop tires

MODEL >>	1060	1360
Capacity	1,060 bushels	1,360 bushels
Width w/o load cells	12' 3"	12' 8"
Length	34' 9"	34' 9"
Height, transport	11' 9"	12' 5"
Tires	900/60R32	520/85R38
Unload auger	21.5"	21.5"
Floor drag auger	13"	13"
PTO	1000 rpm	1000 rpm
Drawbar in short position	Category IV	Category V
Recommended hp	275 hp	275 hp
Weight	18,520 lb	21,280 lb

www.farm-king.com



Farm King

301 Mountain Street South Morden, Manitoba Canada R6M 1X7 Ph.: 204.822.4467 | Fax: 204.822.6348

Toll Free: 888.524.1004 E-mail: info@buhler.com www.farm-king.com

Equipment shown is subject to change without notice. ©2013 BuhlerTrading Inc. Printed in Canada.TSX:BUI Ref: 012013-5000-LM P/N: PCART

